



PRODUCT CERTIFICATE

This is to certify that

Kopine Flooring Systems – Ultralock™ 12 and – Tongue & Groove 12



**BUREAU
VERITAS**

Product description

Kopine Flooring Systems – Ultralock™ 12 and Tongue & Groove 12, are high-density particleboard panels. The supplied glue bonds the panels together to form a continuous flooring membrane and provides an effective seal against moisture. The floors are suitable for use as a floor diaphragm within the scope of NZS 3604:2011 Timber framed buildings.

Product purpose or use

Residential and commercial flooring.

Certificate holder

Kopine Limited
9428 State Highway 26
Kopu, Thames 3578
Ph: 0800 866 678
www.kopine.co.nz

CodeMark Product Certification Body

Bureau Veritas Australia Pty Ltd
3/435 Williamstown Road,
Port Melbourne VIC, 3207
Ph: 1800 855 190
www.bureauveritas.com.au

Sam Guindi
Product Certification Manager

For and on behalf of
Bureau Veritas Australia Pty Ltd

Complies with the New Zealand Building Code (NZBC):

If designed, used, installed and maintained in accordance with the scope of this certificate, the above mentioned product will meet or contribute to meeting the following provisions of the NZBC:

Structure B1.3.1, B1.3.2, B1.3.3 (a)(b)(f)(i)(h)(j)(l)(q), B1.3.4

Durability B2.3.1 (a), B2.3.2 (a)

Hazardous Building Materials F2.3.1

Subject to the following conditions and limitations:

1. Kopine flooring systems shall only be laid in accordance with the Kopine Installation Guide and Technical Specifications (November 2018).
2. The subfloor shall be ventilated and protected from external moisture in accordance with the Kopine Installation Guide and Technical Specifications (November 2018).
3. The flooring shall be protected by a membrane or other impervious finish when installed in wet and splash areas in accordance with the Kopine Installation Guide and Technical Specifications (November 2018).
4. The moisture content of the flooring shall be no more than 18% before sealing or covering with a flooring product.
5. Kopine flooring systems are only suitable for concentrated loads up to 180kg or uniformly distributed loads up to 200kg/m².
6. Exposure to weather should be kept to a minimum, and shall be not more than 12 weeks.



WWW.JAS-ANZ.ORG/REGISTER

30 January 2020
Date of issue

CM70064
Certificate Number



**MINISTRY OF BUSINESS,
INNOVATION & EMPLOYMENT**
HĪKINA WHAKATUTUKI

- This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. The Ministry does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms with the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. The Ministry disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate.
- The certificate holder must maintain compliance with the conditions set out in section 15 of the Building (Product Certification) Regulations 2008. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.